



M20T At-a-glance

LINE SIZE 1½" - 2"

MOTOR 2 hp electric

PUMP 2.1 gpm @ 1,500 psi

All MyTana portable jettors feature:

QUALITY, RELIABLE PUMPS AND MOTORS with thermal protection and accessible controls

PULSE VALVES on all pumps

RUGGED FRAMES which emphasize ergonomics, portability, maneuverability, and stabilization during operation

EASY MAINTENANCE on all components (parts are available for field repairs)


M20T TrapBlast Electric Jetter

The M20T TrapBlast bundles the pump and electric motor in a convenient package suitable for residential jobs and tight spaces.

Customize it with 1/8" hose to start working in 1½" to 2" lines.

- **2 HP industrial motor** works on 15 or 20 amp circuits.
- **Quality AR pump** delivers 2.1 gpm to pull the hose through small lines, pulse valve assists on tight bends and blockages.
- **1/4 turn valve** controls water flow.
- **Quick disconnect fittings** speed set up/tear down.

We design all our jettors so they are easy to load, easy to maneuver, easy to maintain and easy to use.



Powerful. Reliable. Maneuverable.

MyTana jettors are manufactured in the USA and include factory-direct support.

www.MyTana.com ■ (800) 328-8170


M20T Specs

SYSTEM OVERVIEW	
TYPE	Portable, hand carry
LINE SIZE	1.5" - 2" (with 1/8" hose)
WORKING PRESSURE @ pump	Up to 1,500 (with 20 amp circuit)
FLOW RATE	2.1 gpm
APPLICATION type of blockage	General cleaning, soft obstructions – grease, soap
MOTOR	
TYPE	Electric Industrial grade
POWER (HP)	2 hp – 20 amp required for 1,500 psi – 15 amp suitable for 1,200+ psi
STARTER	Toggle switch Water proof
MOTOR/PUMP COUPLING	Direct drive
FRAME	
STYLE	Pump and motor on tray style frame with carry handle Optional transport cart available
FINISH	Steel, powder-coat finish
FEATURES	Anti-skid feet
OPERATING WEIGHT	82 lbs
DIMENSIONS	14" w x 24" d x 13" h

PUMP	
TYPE / HEAD	Triplex Ceramic plunger Forged brass head
FILTER	Replaceable – available online
MAX WATER TEMP	140°

HOSE REEL

N/A — Can be used with stand-alone hose reels or caddies such as our MVRL-SM or MTR-SML available online at mytana.com



HOSE Optional with base purchase	
BRAND	Piranha®
MATERIAL	Reinforced thermoplastic tube Abrasion resistant, polyurethane jacket Quick disconnect fitting
WORKING PRESSURE	4,000
BURST PRESSURE	12,000
TEMP RATING	150° (140° w/ pump)

REQUIRED FOR OPERATION	
POWER SOURCE	20 amp preferred 15 amp acceptable (1,200+ psi) relieve pressure before start up
WATER SOURCE	Household supply at 2.1 gpm (min. 5/8" garden hose)

ADDITIONAL FEATURES

Motor

25 ft power cord
Inline GFCI
Thermal protection

Pump

Pressure regulator / unloader with heavy duty gauge
Pulse valve control
Thermal protection
Quick disconnect fitting for hose hook up



Learn more

See the M20T online at mytana.com/product/m20T



010324

(800) 328-8170
M-F | 7a to 5p CST

[MyTana.com](https://mytana.com)

EMAIL mytana@idexcorp.com



youtube.com/videoMyTana

MYTANA LLC 746 SELBY AVE • ST. PAUL, MN 55104