

M20

FastBlast Electric Jetter

The M20 FastBlast is a versatile jetter that includes a transport cart so you can move the jetter with larger or longer hose in one trip. Customize it with ½" hose and reel and be ready for jobs in up to 4" lines. It can be used with 15 amp circuits (1,200 psi).

 2 HP industrial motor powers up to 1,500 psi cleaning pressure and pulling for smaller lines.

 Quality AR pump has thermal protection, a pulse valve assists in bends and navigating difficult areas.

- **Ball valve** on reel controls water flow.

Remove pump/motor unit to get into tighter spaces.

The M20 is ideal for opening grease-choked or frozen lines.





M20 At-a-glance

LINE SIZE 1½" - 4"

MOTOR 2 HP electric

PUMP 2.1 gpm @ 1,500 psi

All MyTana portable jetters feature:

QUALITY, RELIABLE PUMPS AND MOTORS with thermal protection and accessible controls

PULSE VALVES on all pumps

RUGGED FRAMES which emphasize ergonomics, portability, maneuverability, and stabilization during operation

EASY MAINTENANCE on all components (parts are available for field repairs)

Powerful. Reliable. Maneuverable.

MyTana jetters are manufactured in the USA and include factory-direct support.

www.MyTana.com • (800) 328-8170

M20 Specs

SYSTEM OVERVIEW		
ТҮРЕ	Portable, cart and/or hand carry	
LINE SIZE	1.5" - 4" (with 1/8" and 1/4" hose)	
WORKING PRESSURE @ PUMP	Up to 1,500 (with 20 amp circuit)	
FLOW RATE	2.1 gpm	
APPLICATION type of blockage	General cleaning, ice, softer obstructions, grease, soap	
MOTOR		
ТҮРЕ	Electric Industrial grade	
POWER (HP)	2 hp - 20 amp required for 1,500 psi - 15 amp suitable for 1,200+ psi	
STARTER	Toggle switch Water proof	
MOTOR/PUMP COUPLING	Direct drive	
CART FRAME		
STYLE	Combination – cart/hand carry – pump and motor are mounted on removeable tray frame with carry handle – wheeled transport cart has hose reel	
FINISH	Steel, powder-coat	
WHEELS	Smooth tread pneumatic – rear: (2) 10" – front: (2) 3" swivel w/locking casters	
OPERATING WEIGHT	128 lbs	
DIMENSIONS	20" w x 32" d x 39" h	







PUMP			
TYPE / HEAD	Triplex Ceramic plunger		
	Forged brass head		
FILTER	Replaceable – available online		
MAX WATER TEMP	140°		
HOSE REEL Optional with base purchase			
MAIN REEL CAPACITY	115' of 1/4" jetter hose		
FEATURES	Ball valve on reel		
	Removable		
	Quick disconnect fitting		
	Hand crank		
HOSE Optional with base purchase			
BRAND	Piranha®		
MATERIAL	Reinforced thermoplastic tube		
	Abrasion resistant polyurethane cover		
WORKING PRESSURE	4,000		
BURST PRESSURE	12,000		
TEMP RATING	150° (140° w/ pump)		
REQUIRED FOR OPERATION			
POWER SOURCE	20 amp preferred		
	15 amp acceptable (1,200+ psi) relieve pressure before start up		
WATER SOURCE	Household supply at 2.1 gpm		

ADDITIONAL FEATURES

Pump	Frame
Pressure regulator /	Balanced Weight
	Easy tilt
, 5 5	Loading wheel
Thermal protection	Cord wrap
	Stair glides
	Pressure regulator / unloader with heavy duty gauge Pulse valve control

(min. 5/8" garden hose)



Learn more

See the M20 online at mytana.com/product/m20-jetter



M–F | 7a to 5p CST

