

M20

FastBlast Electric Jetter

The M20 FastBlast is a versatile jetter that includes a transport cart so you can move the jetter with larger or longer hose in one trip. It includes two sizes of hose for work in up to 4" lines. The M20 can be used with 15 amp circuits (1,200 psi).

 2 HP industrial motor powers up to 1,500 psi cleaning pressure and pulling for smaller lines.

 Quality AR pump has thermal protection, a pulse valve assists in bends and navigating difficult areas.

- **Ball valve** on reel controls water flow.

Remove pump/motor unit to get into tighter spaces.

The M20 is ideal for opening grease-choked or frozen lines.



M20 At-a-glance

LINE SIZE 1½" - 4"

MOTOR 2 HP electric

PUMP 2.1 gpm @ 1,500 psi

HOSE 1/4" x 115' 1/8" x 50'

All MyTana portable jetters feature:

QUALITY, RELIABLE PUMPS AND MOTORS with thermal protection and accessible controls

PULSE VALVES on all pumps

RUGGED FRAMES which emphasize ergonomics, portability, maneuverability, and stabilization during operation

EASY MAINTENANCE on all components (parts are available for field repairs)



Powerful. Reliable. Maneuverable.

M20 Specs

SYSTEM OVERVIEW		
TYPE	Portable – cart and/or hand carry	
LINE SIZE	1.5" - 4" (with 1/8" and 1/4" hose)	
WORKING PRESSURE	Up to 1,500 (with 20 amp circuit)	
@ pump	Keep nozzles clean and use spec size/length of hose to maximize pressure at the nozzle	
FLOW RATE	2.1 gpm	
APPLICATION type of blockage	General cleaning, ice, softer obstructions, grease, soap	
MOTOR		
ТҮРЕ	Electric	
	Industrial grade	
POWER (HP)	2 hp	
	20 amp required for 1,500 psi15 amp suitable for 1,200+ psi	
STARTER	Toggle switch	
	Water proof	
MOTOR/PUMP COUPLING	Direct drive	
CART FRAME		
STYLE	Combination – push cart/hand carry – pump and motor are mounted on removeable tray frame with carry handle – wheeled transport cart has hose reel	
CONSTRUCTION	Steel, powder-coat	
WHEELS	Smooth tread pneumatic – rear: (2) 10" – front: (2) 3" swivel w/locking casters	
OPERATING WEIGHT	128 lbs	
DIMENSIONS	20" w x 32" d x 39" h	





39" tall



PUMP	
TYPE / HEAD	Triplex, ceramic plungers Forged brass head
FILTER	Replaceable – available online
FEATURES	Pressure regulator / unloader Pulse valve control Thermal protection
MAX WATER TEMP	140°
HOSE REEL	
FEATURES	Ball valve on reel Removable Quick disconnect fitting Hand crank
HOSE	
INCLUDED Piranha® brand	1/4" NPT x 115 ft 1/8" NPT x 50 ft
MATERIAL	Reinforced thermoplastic tube Abrasion resistant polyurethane cover
WORKING PRESSURE	4,000
BURST PRESSURE	12,000
TEMP RATING	150° (140° w/ pump)
REQUIRED FOR OPERATION	
POWER SOURCE	20 amp preferred 15 amp acceptable (1,200+ psi) relieve pressure before start up
WATER SOURCE	Household supply at 2.1 gpm

ADDITIONAL FEATURES

Motor	Frame	Nozzle Kit
25 ft power cord	Balanced Weight	Get the optional
Inline GFCI	Easy tilt	M20 nozzle kit,
Thermal protection	Loading wheel	see MyTana.com.
	Cord wrap	
	Stair glides	NOZZLE KIT



Learn more

Stair glides

See the M20 online at mytana.com/product/m20-jetter

(min. 5/8" garden hose)



M–F | 7a to 5p CST

